

Carbon Steel Dimensions

API 5L X52 Modified - pipes

NPS IN	O.D. MM	W.T. MM	KG/MT	API-id. SCH.NO
1"	33.4	4.55	3.24	80
		6.35	4.23	160
1.1/2"	48.3	5.08	5.4	80
		7.14	7.23	160
		10.16	9.55	XXS
2"	60.3	3.91	5.44	STD/40
		5.54	7.48	XS/80
		8.74	11.12	160
		11.07	13.45	XXS
		12.7	15	
2.1/2"	73	5.16	8.62	STD/40
		7.01	11.41	XS/80
3"	88.9	5.49	11.29	STD/40
		7.62	15.27	XS/80
		11.13	21.34	160
		15.24	27.67	XXS
		17.5	28.8	
4"	114.3	6.02	16.07	STD/40
		8.56	22.31	XS/80
		11.1	28.3	120
		13.49	33.53	160
		17.12	41.02	XXS
		20	46.5	
		22.2	50.4	
5"	141.3	6.55	21.78	STD/40
		9.52	30.95	XS/80
		12.7	40.2	120
		15.88	49.11	160
		19.05	57.42	XXS
6"	168.3	7.11	28.26	STD/40
		10.97	42.56	XS/80
		12.7	48.73	
		14.27	54.2	120
		18.26	67.56	160
		21.95	79.22	XXS
		25.4	89.5	
		28	96.9	
8"	219.1	31.8	107	
		6.35	33.31	20
		8.18	42.53	STD/40
		10.31	53.1	60
		12.7	64.63	XS/80
		15.88	79.58	
		19.05	93.98	
		22.23	107.92	XXS
		23	111.27	160
		25.4	121.33	
		28	132	
10"	273	31.8	146.88	
		38.1	170.06	
		6.35	41.77	20
		9.27	60.31	STD/40
		12.7	81.55	XS/60
		15.88	100.73	
		19.05	119.3	
		21.44	133.04	120
		25.4	155.15	XXS/140
		28.58	172.33	160
31.75	188.97			
35	205			



Carbon Steel Dimensions

API 5L X52 Modified - pipes

NPS IN	O.D. MM	W.T. MM	KG/MT	API-id. SCH.NO
10"		38.1	220.7	
		45	253	
		50	274.96	
12"	323.8	6.35	49.73	20
		7.14	55.77	
		9.53	73.88	STD
		10.31	79.73	40
		12.7	97.46	XS
		14.27	108.96	60
		15.88	120.62	
		17.48	132.08	80
		19.05	143.21	
		21.44	159.91	100
		25.4	186.97	XXS/120
		31.75	228.74	
		33.32	238.76	160
		38.1	268.43	
45	309.38			
50	337.6			
55	364.57			
14"	355.6	7.92	67.9	20
		9.53	81.33	STD/30
		11.13	94.55	40
		12.7	107.39	XS
		15.88	133.03	
		19.05	158.1	80
		25.4	206.83	
		31.75	253.56	140
		35.71	281.7	160
		38.1	298.3	
		60	437.37	
16"	406.4	7.92	77.83	20
		9.53	93.27	STD/30
		12.7	123.3	XS/40
		14.27	137.99	
		15.88	152.93	
		16.66	160.12	60
		17.48	167.65	
		19.05	181.97	
		21.44	203.53	80
		25.4	238.64	
		31	286	120
		31.75	293.33	
		38.1	346.03	
		61	520	
65	547.23			
18"	457.2	7.92	87.71	20
		9.52	105.1	STD
		12.7	139.15	XS
		15.88	172.74	
		19.05	205.74	60
		23.83	254.67	80
		25.4	270.34	
		31.75	332.95	
		38.1	393.76	
		45.24	459.59	160
20"	508	9.52	117.15	STD/20
		12.7	155.12	XS/30
		15.1	183	40
		15.88	192.71	
		17.48	211.44	
		19.05	229.7	
		23.83	284.52	
		25.4	302.28	

Carbon Steel Dimensions

API 5L X52 Modified - pipes

NPS IN	O.D. MM	W.T. MM	KG/MT	API-id. SCH.NO
20"		26.2	311	
		31.75	372.88	
		32.5	381	
		38.1	441.49	120
		50.8	572.75	160
22"	559	12.7	171.09	XS/30
		15.88	213	
		19.05	253.65	
		25.4	334.23	
		31.75	412.81	
		38.1	489.41	
24"	610	9.52	141.12	STD/20
		12.7	187.06	XS
		14.27	209.64	30
		15.88	232	
		17.48	255.41	40
		19.05	277.61	
		25.4	366.17	
		31.75	452.74	
		38.1	537.33	
		50.8	700.53	

Lengths

Please observe our long double random lengths, giving advantages in connection with welding.

Also reduced consumption of fittings when used for piping.

The above dimensions and weights have been adjusted to conform to ANSI / ASME B36.10M - 1985nor API standard 5L.

